

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone number	1-800-ASHLAND (1-800-274-5263)
Product name	PYROIL® NON-CHLORINATED BRAKE PARTS CLEANER	
Product code	PY40035	
Product Use Description	No data	

2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance: liquid

WARNING! EXTREMELY FLAMMABLE LIQUID AND VAPOR. VAPOR MAY CAUSE FLASH FIRE. MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF INHALED. HARMFUL IF SWALLOWED. MAY CAUSE BLINDNESS. MAY CAUSE EYE, SKIN AND RESPIRATORY TRACT IRRITATION. PROLONGED OR REPEATED CONTACT MAY DRY SKIN, CAUSE IRRITATION AND BURNS.

Potential Health Effects

Exposure routes

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

Eye contact

Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes.

Skin contact

Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Prolonged or repeated contact may dry the skin. Symptoms may include redness, burning, and drying and cracking of skin, skin burns, and other skin damage.

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

Ingestion

Swallowing this material may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

Inhalation

Breathing of vapor or fume is possible. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

Aggravated Medical Condition

Individuals with preexisting heart disorders maybe more susceptible to arrhythmias (irregular heartbeats) if exposed to high concentrations of this material., Exposure to this material may aggravate any preexisting condition sensitive to a decrease in available oxygen, such as chronic lung disease, coronary artery disease or anemias., Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material:, lung (for example, asthma-like conditions), skin, auditory system, liver, kidney, central nervous system, pancreas, Heart, Upper respiratory tract, blood-forming system

Symptoms

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:, stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), metallic taste, central nervous system excitation (giddiness, liveliness, light-headed feeling) followed by central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness) and other central nervous system effects, temporary changes in mood and behavior, Weakness, confusion, runny nose, high blood sugar, loss of appetite, Lack of coordination, irregular heartbeat, narcosis (dazed or sluggish feeling), muscle cramps, pain in the abdomen and lower back, Blurred vision, Shortness of breath, cyanosis (causes blue coloring of the skin and nails from lack of oxygen), visual impairment (including blindness), coma

Target Organs

This material (or a component) shortens the time of onset or worsens the liver and kidney damage induced by other chemicals., Exposure to lethal concentrations of methanol has been shown to cause damage to organs including liver, kidneys, pancreas, heart, lungs and brain. Although this rarely occurs, survivors of severe intoxication may suffer from permanent neurological damage., Prolonged intentional toluene abuse may lead to damage to many organ systems having effects on: central and peripheral nervous systems, vision, hearing, liver, kidneys, heart and blood. Such abuse has been associated with brain damage characterized by disturbances in gait, personality changes and loss of memory. Comparable central nervous system effects have not been shown to result from occupational exposure to toluene., Prolonged intentional toluene abuse may lead to hearing loss progressing to

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

deafness. In addition, while noise is known to cause hearing loss in humans, it has been suggested that workers exposed to organic solvents, including toluene, along with noise may suffer greater hearing loss than would be expected from exposure to noise alone., Overexposure to this material (or its components) has been suggested as a cause of the following effects in laboratory animals:, effects on hearing, liver abnormalities, central nervous system damage, mild, reversible kidney effects, respiratory tract damage (nose, throat, and airways), blood abnormalities, Overexposure to this material (or its components) has been suggested as a cause of the following effects in humans:, visual impairment, kidney damage

Carcinogenicity

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA).

Reproductive hazard

Methanol has caused birth defects in laboratory animals, but only when inhaled at extremely high vapor concentrations. The relevance of this finding to humans is uncertain., Toluene may be harmful to the human fetus based on positive test results with laboratory animals. Case studies show that prolonged intentional abuse of toluene during pregnancy can cause birth defects in humans., This material (or a component) has been shown to cause harm to the fetus in laboratory animal studies. Harm to the fetus occurs only at exposure levels that harm the pregnant animal. The relevance of these findings to humans is uncertain.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous Components	CAS-No.	Concentration
SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC	64742-89-8	>=40-<50%
METHANOL	67-56-1	>=30-<40%
TOLUENE	108-88-3	>=5-<10%
ACETONE	67-64-1	>=5-<10%

4. FIRST AID MEASURES

Eyes

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

Skin

Remove contaminated clothing. Flush exposed area with large amounts of water. If skin is damaged, seek immediate medical attention. If skin is not damaged and symptoms persist, seek medical attention. Launder clothing before reuse.

Ingestion

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

Inhalation

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

Notes to physician

Hazards: Inhalation of high concentrations of this material, as could occur in enclosed spaces or during deliberate abuse, may be associated with cardiac arrhythmias. Sympathomimetic drugs may initiate cardiac arrhythmias in persons exposed to this material. This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. This product contains methanol which can cause intoxication and central nervous system depression. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion. Ethanol competes for the same metabolic pathway and has been used to prevent methanol metabolism. Ethanol administration is indicated in symptomatic patients or at blood methanol concentrations above 20 ug/dl. Methanol is effectively removed by hemodialysis. This material (or a component) has produced hyperglycemia and ketosis following substantial ingestion.

Treatment: No information available.

5. FIRE-FIGHTING MEASURES

Suitable extinguishing media

Dry chemical, Carbon dioxide (CO₂), Water mist

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

Hazardous combustion products

May form: carbon dioxide and carbon monoxide, Hydrocarbons

Precautions for fire-fighting

Material is volatile and readily gives off vapors which may travel along the ground or be moved by ventilation and ignited by pilot lights, flames, sparks, heaters, smoking, electric motors, static discharge or other ignition sources at locations near the material handling point. Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA). Water may be ineffective for extinguishment unless used under favorable conditions by experienced fire fighters. Use water spray to cool fire exposed containers and structures until fire is out if it can be done with minimal risk. Avoid spreading burning material with water used for cooling purposes.

NFPA Flammable and Combustible Liquids Classification

Flammable Liquid Class IB

6. ACCIDENTAL RELEASE MEASURES

Personal precautions

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Ensure adequate ventilation. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Pay attention to the spreading of gases especially at ground level (heavier than air) and to the direction of the wind.

Environmental precautions

Prevent spreading over a wide area (e.g. by containment or oil barriers). Do not let product enter drains. Do not flush into surface water or sanitary sewer system. Local authorities should be advised if significant spillages cannot be contained.

Methods for cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Other information

Suppress (knock down) gases/vapours/mists with a water spray jet. Comply with all applicable federal, state, and local regulations.

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

7. HANDLING AND STORAGE

Handling

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77.

Storage

Store in a cool, dry, ventilated area, away from incompatible substances.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Guidelines

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC		64742-89-8
OSHA Z1	time weighted average	500 ppm
ACGIH	time weighted average	300 ppm
OSHA Z1	time weighted average	2,000 mg/m ³
ACGIH	time weighted average	1,370 mg/m ³
METHANOL		67-56-1
ACGIH	time weighted average	200 ppm
ACGIH	Short term exposure limit	250 ppm
NIOSH	Recommended exposure limit (REL):	200 ppm
NIOSH	Recommended exposure limit (REL):	260 mg/m ³
NIOSH	Short term exposure limit	250 ppm
NIOSH	Short term exposure limit	325 mg/m ³
OSHA Z1	Permissible exposure limit	200 ppm
OSHA Z1	Permissible exposure limit	260 mg/m ³
TOLUENE		108-88-3
ACGIH	time weighted average	20 ppm
NIOSH	Recommended exposure limit (REL):	100 ppm
NIOSH	Recommended exposure limit (REL):	375 mg/m ³

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

NIOSH	Short term exposure limit	150 ppm
NIOSH	Short term exposure limit	560 mg/m3
OSHA Z2	time weighted average	200 ppm
OSHA Z2	Ceiling Limit Value:	300 ppm
OSHA Z2	Maximum concentration:	500 ppm
ACETONE		67-64-1
ACGIH	time weighted average	500 ppm
ACGIH	Short term exposure limit	750 ppm
NIOSH	Recommended exposure limit (REL):	250 ppm
NIOSH	Recommended exposure limit (REL):	590 mg/m3
OSHA Z1	Permissible exposure limit	1,000 ppm
OSHA Z1	Permissible exposure limit	2,400 mg/m3

General advice

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

Exposure controls

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Eye protection

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

Skin and body protection

Wear resistant gloves (consult your safety equipment supplier).
Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

Respiratory protection

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	liquid
Form	no data available
Colour	no data available
Odour	no data available
Boiling point/boiling range	133 °F / 56 °C @ 1,013.23 hPa Calculated Phase Transition Liquid/Gas
Melting point/range	no data available
Sublimation point	no data available
pH	no data available
Flash point	20.12 °F / -6.60 °C Tag closed cup
Ignition temperature	no data available
Evaporation rate	no data available
Lower explosion limit/Upper explosion limit	1.05 %(V) / 36 %(V)
Particle size	no data available
Vapour pressure	307.969 hPa @ 77 °F / 25 °C Calculated Vapor Pressure
Relative vapour density	no data available
Density	0.806 g/cm3 @ 77 °F / 25 °C
Bulk density	No data
Water solubility	no data available
Solubility(ies)	no data available
Partition coefficient: n-octanol/water	no data available
log Pow	no data available
Autoignition temperature	no data available
Viscosity, dynamic	no data available
Viscosity, kinematic	no data available
Solids in Solution	no data available
Decomposition temperature	no data available
Burning number	no data available
Dust explosion constant	no data available
Minimum ignition energy	no data available

10. STABILITY AND REACTIVITY

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

Stability

Stable.

Conditions to avoid

Avoid heat, open flame, and prolonged storage at elevated temperatures.

Incompatible products

Avoid contact with: alkalis, strong acids, strong oxidizing agents, calcium hypochlorite, hypochlorites, Peroxides, sodium, strong bases, Zinc, acids, reducing agents

Hazardous decomposition products

carbon dioxide and carbon monoxide, Hydrocarbons

Hazardous reactions

Product will not undergo hazardous polymerization.

Thermal decomposition

No data

11. TOXICOLOGICAL INFORMATION

Acute oral toxicity

SOLVENT NAPHTHA (PETROLEUM), LIGHT : LD 50 Rat: > 8,000 mg/kg

ALIPHATIC

METHANOL : LD L0 Human: 300 mg/kg

TOLUENE : LD 50 Rat: 2.6 g/kg

ACETONE : LD 50 Rat: 5,800 mg/kg

Acute inhalation toxicity

SOLVENT NAPHTHA (PETROLEUM), LIGHT : LC 50 Rat: 3400 ppm; 4 h

ALIPHATIC

METHANOL : LC 50 Rat: 64000 ppm; 4 h

TOLUENE : LC 50 Rat: 8000 ppm; 4 h
LC 50 Rat: 8,000 mg/l; 4 h
LC 50 Rat: 12,200 mg/l; 2 h

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

ACETONE : LC 50 Rat: > 16000 ppm; 4 h

Acute dermal toxicity

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : LD 50 Rat: > 4,000 mg/kg

METHANOL : LD 50 Rabbit: 12,800 mg/kg

TOLUENE : LD 50 Rabbit: 12,124 mg/kg

ACETONE : LD 50 Rabbit: > 20,000 mg/kg

12. ECOLOGICAL INFORMATION

Biodegradability

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : 99 %
Exposure time: 28 d
Method: OECD Test Guideline 301D

TOLUENE : no data available

ACETONE : no data available

Bioaccumulation

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : Species: Green algae (Chlorella fusca vacuolata)
Exposure time: 24 h
Dose: 0.05 mg/l
Bioconcentration factor (BCF): 28,400
Method: Static

TOLUENE : Species: Ide, silver or golden orfe (Leuciscus idus)
Exposure time: 3 d
Dose: 0.05 mg/l
Bioconcentration factor (BCF): 94
Method: Not reported

**PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035**

ACETONE : no data available

Ecotoxicity effects

Toxicity to fish

SOLVENT NAPHTHA (PETROLEUM), LIGHT
ALIPHATIC
METHANOL

: no data available

: 96 h static test LC 50 Rainbow trout,donaldson trout
(Oncorhynchus mykiss): 18,000.00 - 20,000.00 mg/l

TOLUENE

: 96 h Renewal LC 50 Rainbow trout,donaldson trout
(Oncorhynchus mykiss): 5.80 mg/l
96 h static test LC 50 Fathead minnow (Pimephales
promelas): 12.60 mg/l

ACETONE

: 96 h static test LC 50 Rainbow trout,donaldson trout
(Oncorhynchus mykiss): 4,740.00 - 6,330.00 mg/l
96 h static test LC 50 Bluegill (Lepomis macrochirus):
8,300.00 mg/l
96 h flow-through test LC 50 Fathead minnow
(Pimephales promelas): 8,733.00 - 9,482.00 mg/l

Toxicity to daphnia and other aquatic invertebrates.

SOLVENT NAPHTHA (PETROLEUM), LIGHT
ALIPHATIC
METHANOL

: no data available

: 48 h static test EC 50 Water flea (Daphnia magna): >
10,000.00 mg/l

TOLUENE

: 48 h static test EC 50 Water flea (Daphnia magna):
6.00 mg/l

ACETONE

: no data available

Toxicity to algae

SOLVENT NAPHTHA (PETROLEUM), LIGHT
ALIPHATIC
METHANOL

: no data available

: no data available

TOLUENE

: no data available

**PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035**

ACETONE : no data available

Toxicity to bacteria

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : no data available

TOLUENE : no data available

ACETONE : no data available

Biochemical Oxygen Demand (BOD)

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : no data available

TOLUENE : no data available

ACETONE : no data available

Chemical Oxygen Demand (COD)

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : no data available

TOLUENE : no data available

ACETONE : no data available

Additional ecological information

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC : no data available

METHANOL : no data available

TOLUENE : no data available

ACETONE : no data available

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

13. DISPOSAL CONSIDERATIONS

Waste disposal methods

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

14. TRANSPORT INFORMATION

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT /LTD. QTY.
-----------	----------------------	---------------	--------------------	---------------	-----------------------------

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN 1992	LIQUIDO INFLAMABLE, TOXICO, N.E.P. (ACETONE, METHANOL)	3	(6.1)	II	
---------	--	---	-------	----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

UN 1992	Flammable liquid, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

UN 1992	Flammable liquid, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

INTERNATIONAL MARITIME DANGEROUS GOODS

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

TRANSPORT CANADA - INLAND WATERWAYS

UN 1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II	
---------	---	---	-------	----	--

TRANSPORT CANADA - RAIL

ASHLAND
SAFETY DATA SHEET

Page: 14
Revision Date: 12/09/2010
Print Date: 1/25/2011
MSDS Number: R0253095
Version: 4.0

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

UN	1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

TRANSPORT CANADA - ROAD

UN	1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (ACETONE, METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

U.S. DOT - INLAND WATERWAYS

UN	1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

U.S. DOT - RAIL

UN	1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

U.S. DOT - ROAD

UN	1992	Flammable liquids, toxic, n.o.s. (ACETONE, METHANOL)	3	(6.1)	II
----	------	---	---	-------	----

*ORM = ORM-D, CBL = COMBUSTIBLE LIQUID

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

15. REGULATORY INFORMATION

California Prop. 65

WARNING! This product contains a chemical known to the State of California to cause cancer.	BENZENE
WARNING! This product contains a chemical known to the State of California to cause birth defects or other reproductive harm.	TOLUENE BENZENE

SARA Hazard Classification

Fire Hazard
Acute Health Hazard

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

SARA 313 Component(s)

METHANOL 36.88 %
TOLUENE 9.97 %

New Jersey RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC 64742-89-8
METHANOL 67-56-1
TOLUENE 108-88-3
ACETONE 67-64-1

Pennsylvania RTK Label Information

SOLVENT NAPHTHA (PETROLEUM), LIGHT ALIPHATIC 64742-89-8
METHANOL 67-56-1
TOLUENE 108-88-3
ACETONE 67-64-1

Notification status

US. Toxic Substances Control Act y (positive listing)
Australia. Industrial Chemical (Notification and Assessment) Act y (positive listing)
Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL). (Can. Gaz. Part II, Vol. 133) y (positive listing)
Japan. Kashin-Hou Law List y (positive listing)
Korea. Toxic Chemical Control Law (TCCL) List y (positive listing)
Philippines. The Toxic Substances and Hazardous and Nuclear Waste Control Act y (positive listing)
China. Inventory of Existing Chemical Substances y (positive listing)
New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand n (Negative listing)

Reportable quantity - Product

US. EPA CERCLA Hazardous Substances (40 CFR 302) 10026 lbs

Reportable quantity-Components

TOLUENE 108-88-3 1000 lbs

	HMIS	NFPA
Health	2*	2
Flammability	3	3

ASHLAND
SAFETY DATA SHEET

Page: 16
Revision Date: 12/09/2010
Print Date: 1/25/2011
MSDS Number: R0253095
Version: 4.0

PYROIL® NON-CHLORINATED BRAKE
PARTS CLEANER
PY40035

Physical hazards	0	
Instability		0
Specific Hazard	--	--

16. OTHER INFORMATION

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).