

PYROIL® PENETRATING OIL  
596555

**I. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

Ashland	Regulatory Information Number	1-800-325-3751
P.O. Box 2219	Telephone	614-790-3333
Columbus, OH 43216	Emergency telephone	1-800-ASHLAND (1-800-274-5263)

Product name	PYROIL® PENETRATING OIL
Product code	596555
Product Use Description	No data

**2. HAZARDS IDENTIFICATION**

**Emergency Overview**

Appearance: liquid

CAUTION! MAY AFFECT THE CENTRAL NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. MAY BE HARMFUL IF SWALLOWED. CAUSES EYE IRRITATION.

**Potential Health Effects**

**Exposure routes**

Inhalation, Skin absorption, Skin contact, Eye Contact, Ingestion

**Eye contact**

Can cause severe eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can injure eye tissue.

**Skin contact**

May cause mild skin irritation. Symptoms may include redness and burning of skin. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use.

**Ingestion**

Swallowing small amounts of this material during normal handling is not likely to cause harmful effects. Swallowing large amounts may be harmful. This material can get into the lungs during swallowing or vomiting. This results in lung inflammation and other lung injury.

PYROIL® PENETRATING OIL,  
596555

**Inhalation**

Breathing aerosol and/or mist is possible when material is sprayed. Aerosol and mist may present a greater risk of injury because more material may be present in the air than from vapor alone. Breathing small amounts of this material during normal handling is not likely to cause harmful effects. Breathing large amounts may be harmful. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.).

**Aggravated Medical Condition**

Preexisting disorders of the following organs (or organ systems) may be aggravated by exposure to this material: skin, lung (for example, asthma-like conditions)

**Symptoms**

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include: stomach or intestinal upset (nausea, vomiting, diarrhea), irritation (nose, throat, airways), central nervous system depression (dizziness, drowsiness, weakness, fatigue, nausea, headache, unconsciousness), shortness of breath, loss of coordination, lung edema (fluid buildup in the lung tissue), Convulsions

**Target Organs**

Diethylene glycol monobutyl ether has been found to cause breakage of red blood cells following ingestion in rats. Injury to other organs including liver and kidneys was considered secondary to the effect on the blood.

**Carcinogenicity**

This material is not listed as a carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP), or the Occupational Safety and Health Administration (OSHA). This product (or a component) is a petroleum-derived material. Similar materials and certain compounds occurring naturally in petroleum oils have been shown to cause skin cancer in laboratory animals following repeated exposure without washing or removal.

**Reproductive hazard**

Diethylene glycol monobutyl ether did not cause harm to the fetus when given orally or when applied to the skin in laboratory animal studies.

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

PYROIL® PENETRATING OIL  
596555

<b>Components</b>	<b>CAS-No.</b>	<b>Concentration</b>
MINERAL SEAL OIL	64741-44-2	>=80-<90%
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHT	64742-53-6	>=10-<15%
DIETHYLENE GLYCOL	112-34-5	>=1.5-<5%
MONOBUTYL ETHER		
CARBON DIOXIDE	124-38-9	>=1.5-<5%

**4. FIRST AID MEASURES****Eyes**

If symptoms develop, immediately move individual away from exposure and into fresh air. Flush eyes gently with water for at least 15 minutes while holding eyelids apart; seek immediate medical attention.

**Skin**

Remove contaminated clothing. Wash exposed area with soap and water. If symptoms persist, seek medical attention. Launder clothing before reuse.

**Ingestion**

Seek medical attention. If individual is drowsy or unconscious, do not give anything by mouth; place individual on the left side with the head down. Contact a physician, medical facility, or poison control center for advice about whether to induce vomiting. If possible, do not leave individual unattended.

**Inhalation**

If symptoms develop, move individual away from exposure and into fresh air. If symptoms persist, seek medical attention. If breathing is difficult, administer oxygen. Keep person warm and quiet; seek immediate medical attention.

**Notes to physician**

**Hazards:** This material is an aspiration hazard. Potential danger from aspiration must be weighed against possible oral toxicity (See Section 2 - Swallowing) when deciding whether to induce vomiting. Diglycol ethers may cause acidosis.

**Treatment:** No information available.

**5. FIRE-FIGHTING MEASURES**

PYROIL® PENETRATING OIL  
596555

**Suitable extinguishing media**

Water mist, Carbon dioxide (CO<sub>2</sub>), Dry chemical

**Hazardous combustion products**

carbon dioxide and carbon monoxide, various hydrocarbons

**Precautions for fire-fighting**

Never use welding or cutting torch on or near drum (even empty) because product (even just residue) can ignite explosively. Wear full firefighting turn-out gear (full Bunker gear), and respiratory protection (SCBA).

**Flammability Class for Flammable Liquids**

Combustible Liquid Class IIIB

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions**

For personal protection see section 8. Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed. Eliminate all ignition sources (flares, flames including pilot lights, electrical sparks). Eliminate all sources of ignition such as flares, flames (including pilot lights), and electrical sparks. Persons not wearing proper personal protective equipment should be excluded from area of spill.

**Environmental precautions**

Prevent run-off to sewers, streams or other bodies of water. If run-off occurs, notify proper authorities as required, that a spill has occurred.

**Methods for cleaning up**

Absorb liquid on vermiculite, floor absorbent or other absorbent material.

**7. HANDLING AND STORAGE**

**Handling**

Containers of this material may be hazardous when emptied. Since emptied containers retain product residues (vapor, liquid, and/or solid), all hazard precautions given in the data sheet must be observed. Avoid prolonged or frequently repeated skin contact with this material. Skin contact can be minimized by wearing impervious protective gloves. As with all products of this nature, good personal hygiene is essential. Hands and other exposed areas should be washed thoroughly with soap and water after

PYROIL® PENETRATING OIL  
596555

contact, especially before eating and/or smoking. Regular laundering of contaminated clothing is essential to reduce indirect skin contact with this material. Static ignition hazard can result from handling and use. Electrically bond and ground all containers, personnel and equipment before transfer or use of material. Special precautions may be necessary to dissipate static electricity for non-conductive containers. Use proper bonding and grounding during product transfer as described in National Fire Protection Association document NFPA 77. Hydrocarbon solvents are basically non-conductors of electricity and can become electrostatically charged during mixing, filtering or pumping at high flow rates. If this charge reaches a sufficiently high level, sparks can form that may ignite the vapors of flammable liquids. Warning. Sudden release of hot organic chemical vapors or mists from process equipment operating at elevated temperature and pressure, or sudden ingress of air into vacuum equipment, may result in ignitions without the presence of obvious ignition sources. Published "autoignition" or "ignition" temperature values cannot be treated as safe operating temperatures in chemical processes without analysis of the actual process conditions. Any use of this product in elevated temperature processes should be thoroughly evaluated to establish and maintain safe operating conditions.

**Storage**

Do not store near extreme heat, open flame, or sources of ignition. Do not store in temperatures above 120 degrees F.

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

**Exposure Guidelines**

<b>DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHT</b>		<b>64742-53-6</b>	
OSHA Z1	Permissible exposure limit	500 ppm	
OSHA Z1	Permissible exposure limit	2,000 mg/m <sup>3</sup>	
OSHA Z1A	time weighted average	400 ppm	
OSHA Z1A	time weighted average	1,600 mg/m <sup>3</sup>	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	400 ppm	
US CA OEL	Time Weighted Average (TWA) Permissible Exposure Limit (PEL):	1,600 mg/m <sup>3</sup>	
ACGIH	time weighted average	5 mg/m <sup>3</sup>	Mist.
ACGIH	Short term exposure limit	10 mg/m <sup>3</sup>	Mist.

PYROIL® PENETRATING OIL  
596555

ACGIH NIC                      time weighted average                      0.2 mg/m<sup>3</sup>                      Inhalable fraction.

<b>CARBON DIOXIDE</b>		<b>124-38-9</b>
ACGIH	time weighted average	5,000 ppm
ACGIH	Short term exposure limit	30,000 ppm
NIOSH	Recommended exposure limit (REL):	5,000 ppm
NIOSH	Recommended exposure limit (REL):	9,000 mg/m <sup>3</sup>
NIOSH	Short term exposure limit	30,000 ppm
NIOSH	Short term exposure limit	54,000 mg/m <sup>3</sup>
OSHA Z1	Permissible exposure limit	5,000 ppm
OSHA Z1	Permissible exposure limit	9,000 mg/m <sup>3</sup>

**General advice**

These recommendations provide general guidance for handling this product. Personal protective equipment should be selected for individual applications and should consider factors which affect exposure potential, such as handling practices, chemical concentrations and ventilation. It is ultimately the responsibility of the employer to follow regulatory guidelines established by local authorities.

**Exposure controls**

Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

**Eye protection**

Wear chemical splash goggles when there is the potential for exposure of the eyes to liquid, vapor or mist.

**Skin and body protection**

Wear resistant gloves (consult your safety equipment supplier). Wear normal work clothing including long pants, long-sleeved shirts and foot covering to prevent direct contact of the product with the skin. Launder clothing before reuse. If skin irritation develops, contact your facility health and safety professional or your local safety equipment supplier to determine the proper personal protective equipment for your use.

**Respiratory protection**

PYROIL® PENETRATING OIL  
596555

A NIOSH-approved air-purifying respirator with an appropriate cartridge and/or filter may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits (if applicable) or if overexposure has otherwise been determined. Protection provided by air-purifying respirators is limited. Use a positive pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where an air-purifying respirator may not provide adequate protection.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

<b>Physical state</b>	liquid
<b>Form</b>	aerosol
<b>Colour</b>	No data
<b>Odour</b>	No data
<b>Boiling point/boiling range</b>	204.44 °C / 399.99 °F@ 1,013.33 hPa
<b>pH</b>	No data
<b>Flash point</b>	No data
<b>Evaporation rate</b>	No data
<b>Explosion limits</b>	No data
<b>Vapour pressure</b>	No data
<b>Vapour density</b>	No data
<b>Density</b>	0.813 g/cm <sup>3</sup> @ 60.1 °F / 15.6 °C
<b>Solubility</b>	No data
<b>Partition coefficient: n-octanol/water</b>	No data
<b>log Pow</b>	no data available
<b>Autoignition temperature</b>	No data

**10. STABILITY AND REACTIVITY****Stability**

Stable.

**Conditions to avoid**

Heat, flames and sparks.

**Incompatible products**

strong oxidizing agents

PYROIL® PENETRATING OIL  
596555

**Hazardous decomposition products**

carbon dioxide and carbon monoxide, various hydrocarbons

**Hazardous reactions**

Product will not undergo hazardous polymerization.

**Thermal decomposition**

No data

**11. TOXICOLOGICAL INFORMATION**

**Acute oral toxicity**

MINERAL SEAL OIL	LD 50 Rat: > 5 g/kg
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHT	LD 50 Rat: > 5 g/kg
DIETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rat: 6,560 mg/kg
CARBON DIOXIDE	no data available

**Acute inhalation toxicity**

MINERAL SEAL OIL	LC 50 Rat: 1,700 mg/m <sup>3</sup> , 4 h
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHT	no data available
DIETHYLENE GLYCOL MONOBUTYL ETHER	no data available
CARBON DIOXIDE	no data available

**Acute dermal toxicity**

MINERAL SEAL OIL	LD 50 Rabbit: > 2 g/kg
DISTILLATES (PETROLEUM), HYDROTREATED LIGHT NAPHT	LD 50 Rabbit: > 2,001 mg/kg
DIETHYLENE GLYCOL MONOBUTYL ETHER	LD 50 Rabbit: 2,700 mg/kg
CARBON DIOXIDE	no data available

**12. ECOLOGICAL INFORMATION**

**Aquatic toxicity**

PYROIL® PENETRATING OIL  
596555

**Acute and Prolonged Toxicity to Fish**

No data

**Acute Toxicity to Aquatic Invertebrates**

No data

**Environmental fate and pathways**

No data

**13. DISPOSAL CONSIDERATIONS**

**Waste disposal methods**

Dispose of in accordance with all applicable local, state and federal regulations. For assistance with your waste management needs - including disposal, recycling and waste stream reduction, contact Ashland Distribution's Environmental Services Group at 800-637-7922.

**14. TRANSPORT INFORMATION**

**IMDG:**

UN1950, AEROSOLS 2.1,

**IATA\_P:**

UN1950, Aerosols, flammable 2.1,

**IATA\_C:**

UN1950, Aerosols, flammable 2.1,

**CFR\_ROAD:**

UN1950, Aerosols 2.1,

**CFR\_RAIL:**

UN1950, Aerosols 2.1,

**CFR\_INWTR:**

UN1950, Aerosols 2.1,

**IMDG\_ROAD:**

UN1950, AEROSOLS 2.1,

**IMDG\_RAIL:**

UN1950, AEROSOLS 2.1,

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.



**ASHLAND**  
**SAFETY DATA SHEET**

Page: 11

Revision Date: 11/11/2009

Print Date: 1/25/2011

MSDS Number: 000000023124

Version: 1.10

PYROIL® PENETRATING OIL  
596555

<b>HMIS</b>	2	2	0
<b>NFPA</b>	2	2	0

**16. OTHER INFORMATION**

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This MSDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).